Smart Payment Terminal

# SUNMI P3 MIX

MIX, the all-in-one enterprise tablet.



## MIX your POS terminal to capture businesses anywhere, anytime.

10"high-resolution display and a built-in high speed printer make a mobile and desktop terminal.

### MIX, design not only for payment.

Ergonomically designed for a comfortable grip. Professional scanner integrated 1D/2D barcode scanning. Aluminum-magnesium alloy frame and incell touchscreen make it strong yet slim and light.

#### MIX for higher performance.

Qualcomm hexa-core processor and 4GB RAM+32GB ROM for an assured strong performance.

#### MIX for wider extensibility.



Specially designed rotatable functional cradle enable cash drawer, handheld scanner and network among other accessories that boost your business. \*Both rotatable cradle and non-rotatable cradle options are available.





### Accept any payment methods to ensure secure and stable payment processing.



All Pictures shown are for illustration purpose only, actual product may vary.

#### **SUNMI P3 MIX Application Scenario**



**Tableside Ordering** 



**One-on-one Service** 



**Drive Thru** 

### SUNMI P3 MIX Tech Specs

#### **General Configuration**

**Product Model** os Processor Memory Display SUNMI OS 4.0 Qualcomm hexa-core 2.4/2.0GHz 10.1" HD 1280\*800 IPS (based on Android 13) IC Card Scanner Camera **Magstripe Reader** NFC Reader Front: 2MP FF QR Payment: 0.3MP FF Smart IC card/logic encryption contact card; ISO 7816/EMV/compliant; 2D professional scanner Type A&B card, MIFARE card, ISO/IEC 14443 and ISO 15693 compliant Bi-directional card reading; ISO 7810/7811 compliant Network Wi-Fi Bluetooth GPS Card Slot 2.4GHz/5GHz IEEE 802.11 a/b/g/n/ac 2\*Nano SIM+2\*SAM 1\*MicroSD **Power Adapter** Battery Ports **Button** Speaker Removable Lithium battery 7.2V/2600mAh Input: AC 100 ~ 240V Output: DC 5V / 2A 1\* Type-C 1\* Type-A 1\*Power on/off button Dimensions(L\*W\*H) Cradle Customer Display (optional) **Total Weight** Cradle (optional) Fingerprint 3\*USB Type A, RJ11, RJ45 Support USB OTG 246\*231\*73mm 670g 58mm/710g 80mm Environment Operating temperature: 0°C ~ 45°C Storage temperature: -20°C ~ 60°C **58 Version** 80 Version Built-in 58mm thermal printer Built-in 80mm thermal printer Print speed: 70mm/s Print speed: 70mm/s Printer Paper roll: Φ40mm Paper roll: Φ40mm

Printer life: 100km

1.All specifications are subject to change without (prior) notice

Printer life: 100km